

Projecteur IR



IKA-IR060/60
IKA-IR080/30
IKA-IR150/15




IKA-IR04/160

	IKA-IR060/60	IKA-IR080/30	IKA-IR150/15	IKA-IR04/160
Distance	60 m	80 m	150 m	4 m
Angle	60°	30°	15°	160°
Alimentation	12V	12V	12V	12V
Consommation	1200mA	1200mA	1200mA	1000mA
Température d'utilisation	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C
Dimension de caméra	Φ103 x 150 x 140 mm	Φ103 x 150 x 140 mm	Φ103 x 150 x 140 mm	Φ105 x 75 mm
Poids	700 g	700 g	700 g	700 g


Alimentation



IKA-DC120504/2



IKA-DC120509/1



IKA-DC121009/2



IKA-DC121018/1

	IKA-DC120504/2	IKA-DC120509/1	IKA-DC121009/2	IKA-DC121018/1
Entrée	220V AC	220V AC	220V AC	220V AC
Sortie	12V DC	12V DC	12V DC	12V DC
Puissance	5A	5A	10A	10A
Nombre de voie	4	9	9	18
Protection PTC	2A	1A	2A	1A
Dimension	250 x 210 x 95 mm	250 x 210 x 95 mm	250 x 210 x 95 mm	250 x 210 x 95 mm
Poids	2,1 kg	2,1 kg	2,1 kg	2,3 kg



IKONIC

Z.I de la Bonde
15, rue du Buisson aux Fraises
91300 Massy FRANCE

Email info@ikonnic.fr
Site www.ikonnic.fr