



IKC-CVI21
1.3M Pixel

IKC-CVI22
2.0M Pixel

Capteur	1/3" CMOS 1.3M CMOS	1/3" CMOS 2M CMOS
Nombre de pixels	1280(H) x 960(V)	1920(H) x 1080(V)
Sensibilité	0.1 Lux / F1.2 (couleur), 0.01 Lux / F1.2 (NB), 0 Lux (IR ON)	0.1 Lux / F1.2 (couleur), 0.01 Lux / F1.2 (NB), 0 Lux (IR ON)
Objectif	6mm (2.8mm, 3.6mm, 6mm, 8mm)	6mm (2.8mm, 3.6mm, 6mm, 8mm)
Compression Vidéo	H.264 / MJPEG / JPEG	H.264 / MJPEG / JPEG
Résolution Image	25 / 50 IPS @ 720P(1280x720)	25 IPS @ 1080P(1920x1080), 25 / 50 IPS @ 720P(1280x720)
Contrôle Iris	Auto / Manuel	Auto / Manuel
Jour / Nuit	OUI	OUI
Réduction bruit	3D / 2D	3D / 2D
LED Infrarouge	30m, IP66	30m, IP66
Alimentation	12V DC / PoE	12V DC / PoE
Consommation	>4.2W	>4.2W
Environnement d'utilisation	Température : -10°C ~ +50°C, Humidité : 10% ~ 90%	Température : -10°C ~ +50°C, Humidité : 10% ~ 90%
Distance de Transmission	>500m via câble coaxial HR6 R	>500m via câble coaxial HR6 R
Dimension de caméra	65mm x 154.7mm	65mm x 154.7mm
Poids	0.38kg	0.38kg

