



IKC-IR30PP/BK



IKC-IR50PK/BK

	IKC-IR30PP/BK	IKC-IR50PK/BK
Capteur	1/3" Sony 960H CCD, DSP Effio-P WDR	1/3" Sony 960H CCD, DSP Effio-P WDR
Nombre de pixels	976H x 582V	976H x 582V
Résolution	700 TVL	700 TVL
Sensibilité	0,003 lux/F1,2	0,003 lux/F1,2
Objectif	3.3-12mm, Auto-Iris, 79.3° ~ 29.8°	6-50mm, Auto-Iris, 48° ~ 6°
LED IR	LED IR (13 + 2), 850nm	6 LED IR, 850nm
Portée	30m	50m
Jour / Nuit	OUI, IR-Cut	OUI, IR-Cut
Signal / Bruit	> 52dB	> 52dB
Balance de blanc	ATW	ATW
Alimentation	12V DC	12V DC
Consommation	150mA (510mA IR avec LED allumé)	140mA (900mA IR avec LED allumé)
Température d'utilisation	-10°C --- +55°C	-10°C --- +55°C
Norme d'étanchéité	IP66	IP66
Dimension de caméra	Φ=80mm, L=265mm	Φ=103mm, L=377mm
Dimension du pare-soleil	Largeur=69mm, L=265mm	Largeur=110mm, L=377mm
Poids	680g	1650g
Matière	Alluminium	Alluminium
Support	3 Axes	3 Axes

